

MC-SY02

Horno eléctrico de secado de aire caliente (AUTOCLAVE)



MC-SY02

Internal frame and hardware

High-quality stainless steel rivet hardware is used, with a high cost-performance, not easily rusted and high in strength.



Partition

The removable partition can be adjusted in height, which increases the available space for use.



Handle

This new type handle is easy to open and close, conforms to ergonomics, and feels comfortable to grip.



Observation window

Equipped with a double-layered glass observation window that allows to observe the indoor work status at any time.



Material

The cabinet body is made of thick cold-rolled steel plate, which is sturdy and reliable. The inner chamber is made of stainless steel, and the four corners are semi-circular, which is easy to clean.



Alertor

Digital display running time, automatic alarm when work is finished, temperature overheat alarm.



Circulation system

The hot air circulation system is composed of low-noise fans and suitable air ducts, which result in uniform temperature inside the cabinet.



Sealing

There is a silicone rubber seal between the inner chamber and the tempered glass to ensure the sealing of the door and the inner space.



Surface treatment

Electrostatic spraying shell, does not peel off paint, corrosion-resistant.



Temperature control

Microcomputer temperature control, with dual digital display for setting and measuring temperature, as well as PID self-tuning function. Temperature control accuracy reaches 0.1°C, for even more precise control.



Parámetros técnicos:

- Volumen: 70L
- Tamaño del estudio (mm) : 450x350x450
- Potencia: 1000W
- Rango de control de temperatura: 50~300°C
- Precisión de temperatura: 0,1°C
- Fluctuación de temperatura: $\pm 1^\circ\text{C}$
- Tiempo: 0-999 min
- Fuente de alimentación: 110V 60Hz / 220V 50Hz
- Tamaño de la máquina (mm): 620x680x620 peso neto
- Tamaño del embalaje (mm): 720x750x740 peso neto
- Peso bruto/Peso neto: 62/48kg

Entrega Inmediata